

CP-UVR-1601E2-V3

16 Ch. Tribrid 720P HDCVI DVR



Main Features

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 2 SATA HDD up to 12TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



*Product casing and specifications are subject to change without prior notice

CP- UVR-1601E2-V3

16 Ch. Tribrid 720P HDCVI DVR



Feature

Processor
 Operating System
 Two-way Talk
 User Interface
 Video Input
 Video Output
 Video Standard
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Privacy Masking
 Audio Input
 Audio Output
 Motion Detection
 Video Loss
 Camera Blank
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Record Interval
 Interface Ports
 Ethernet
 Protocols

Specification

Embedded processor
 Embedded LINUX
 Reuse audio input/output channel 1
 GUI
 16 channel, BNC
 1 HDMI, 1 VGA
 Analog: NTSC/PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 16+2 up to 5Mp
 H.264 / G.711
 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768, 800×600
 Main Stream: 1*1080N(1~25/30fps)+15*(1~12fps)/1*720P(1~25/30fps)+15*(1~15fps)/960H/
 D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Extra Stream: CIF/QCIF(1~7fps)
 1/4/8/9/16
 4 rectangular zones (each camera)
 1 channel, RCA
 1 channel, RCA
 Supports
 Supports
 Supports
 iPhone, iPad, Android, Windows Phone
 2 SATA port, up to 12TB
 Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
 Manual, Schedule(Regular(Continuous), MD), Stop
 Time/Date, MD & Exact search (accurate to second)
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
 USB Device/Internal SATA burner/Network
 128 users
 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
 RJ-45 port (10/100M)
 HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P, ONVIF Version 2.4 conformance



*Product casing and specifications are subject to change without prior notice

CP- UVR-1601E2-V3

16 Ch. Tribrid 720P HDCVI DVR



Feature

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

DC12V/4A

15W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 55mm

2.35Kg(without HDD)