

CP-UVR-0401E1S-V3**4 Ch. 720P HDCVI DVR****Main Features**

- Support HDCVI/Analog/IP Video input
- All channel 1080N/720P Realtime Recording
- H.264 dual-stream Video Compression
- HDMI / VGA Simultaneous Video Output
- Support 1 SATA HDD up to 6TB, 2 USB2.0
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



**Product casing and specifications are subject to change without prior notice*

CP- UVR-0401E1S-V3

4 Ch. 720P HDCVI DVR



Feature

Processor
Operating System
Two-way Talk
User Interface
Video Input
Video Output
Video Standard
Compression
Video Resolution
Video Recording
Video Display Split
Privacy Masking
Audio Input
Audio Output
Motion Detection
Video Loss
Camera Blank
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Max User Account
Interface Ports
Record Interval
Ethernet
Protocols
Power Supply
Power Consumption

Specification

Embedded processor
Embedded LINUX
Reuse audio input/output channel 1
GUI
4 channel,BNC
1 HDMI, 1 VGA
Analog: NTSC/ PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 4+1 up to 5MP
H.264 / G.711
1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
Main Stream:1080N/720P/960H/D1/HD1/BCIF/CIF/QCIF(1~25/30fps), Extra Stream: CIF/QCIF (1~15fps)
1/4/6
4 rectangular zones (each camera)
1 channel, RCA
1 channel, RCA
Supports
Supports
Supports
iPhone, iPad, Android, Windows Phone
1 SATA port, up to 6TB
Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips
Manual, Schedule(Regular(Continuous), MD), Stop
Time/Date, MD & Exact search (accurate to second)
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file,
USB Device/Internal SATA burner/Network
128 users
1 HDMI, 1 VGA, 2 USB2.0, 1 RS485
1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
RJ-45 port (10/100M)
HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
DC12V/1.5A
10W(without HDD)



*Product casing and specifications are subject to change without prior notice



CP- UVR-0401E1S-V3

4 Ch. 720P HDCVI DVR



Feature

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

Smart 1U, 205 mm×205 mm×40 mm

0.5KG(without HDD)



**Product casing and specifications are subject to change without prior notice*