

CP- VNC-T4KZR10-VMD

4K WDR Array Bullet Camera - 100Mtr.

INDIGO



Main Features

- 1/2.5" 8MP PS CMOS Image Sensor
- Max 30fps@4K
- H.265, H.264, MJPEG Triple-stream encoding
- WDR (120dB), Day/Night (ICR), Corridor mode, 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8~12mm Motorized Lens
- IR Range of 100 Mtrs, Micro SD Card, IP67, PoE
- Supports Instastream technology, save disk space and bandwidth upto 70%
- Mobile Software: Android, iOS
- CMS Software: IVMS



InstaStream

CE FCC RoHS COMPLIANT

*Product casing and specifications are subject to change without prior notice

CP- VNC-T4KZR10-VMD

4K WDR Array Bullet Camera - 100Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control (AGC)
Video Compression
S/N Ratio
Video Streaming
Resolution
Video Output
Frame Rate
Privacy Mask
ICR
ROI
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
WDR
Protocol
Smart Detection
Ethernet
IR
OSD
Interface Ports
Micro SD
Audio
Operating Temperature

Specification

1/2.5" 8MP Progressive scan CMOS
Colour: 0.02 Lux (F1.6, AGC ON) 0 Lux with IR
Auto/Manual, 1/6~1/100000s
Auto/Manual
2.8~12mm Motorized Lens
Auto/Manual
H.265, H.264, MJPEG
>55dB
Triple
3840x2160
1 BNC, impedance 75Ω; amplitude 1 V [p-p]
Max.30 fps@4K (3840x2160) , Max. 30 fps@1080P (1920x1080)
Up to 8 areas
IR-cut filter with auto switch (ICR)
Supports
impedance 35 kΩ; amplitude 2 V [p-p]
impedance 600Ω; amplitude 2 V [p-p]
G.711
2 Ch. IN
1 Ch. Out
Optical WDR (Upto 120dB)
IPv4, IGMP, ICMP, ARP, TCP, UDP,L2TP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, ONVIF, API
Intrusion, crossing line, Motion detection, Audio detection, Face detection, Defocus, Scene Change, People counting
1 RJ45 10M/100M Base-TX Ethernet
Array Range of 100 Mtr.
Up to 8 OSDs
1 RS485
Micro SD, Up to 128 GB
Two-way audio Supported
-40°C ~ +60°C (-40°F ~ 140°F)



CP- VNC-T4KZR10-VMD

4K WDR Array Bullet Camera - 100Mtr.



Feature

Humidity

Power Source

Power Consumption

Weatherproof Standard

Dimension

Weight

Specification

≤ 95% RH (non-condensing)

DC12V±25%, AC24V±25% or PoE (IEEE802.3 at)

Max. 15W

IP67

305.5mm x 104.1mm x 97.3mm (12.0" x 4.1" x 3.8")

1.65 kg